

# L SERIES

EV CHARGER



- L07P      7.3kW      SINGLE-PHASE
- L11P      11kW      THREE-PHASE



## ROBUST DURABILITY

IP55 and IK08 protection for reliable performance.



## SMART CONNECTIVITY

Connect via Bluetooth, or Wi-Fi.



## SOLAR LINKAGE

PV power can be used directly.



## SCHEDULED TIME CHARGING

Set the charging time as you wish.



## RENEWABLE ENERGY COMPATIBILITY

Direct surplus solar power for EV charging.



# TECHNICAL SPECIFICATIONS

MODEL	L07P	L11P
TYPE	CHARGING PLUG	CHARGING PLUG
<b>INPUT</b>		
Wiring Scheme	1P+N+PE	3P+N+PE
Voltage [Vac]	230±20%	400±20%
Maximum Current [A]	32	16
Frequency [Hz]	50/60	
<b>OUTPUT</b>		
Voltage [Vac]	230±20%	400±20%
Maximum Current [A]	32	16
Rated Power [kW]	7.3	11
<b>USER INTERFACE &amp; CONTROL</b>		
Connector Type	Type 2 plug	
Start Mode	Plug&Charge/App	
<b>COMMUNICATION</b>		
Bluetooth	Yes	
Wifi (2.4GHz)	Yes	
<b>ENVIRONMENT</b>		
Installation	Wall-mount / Post-mount	
Operating Temperature [°C]	-25 ~ 50	
Operating Humidity [%]	5 ~ 95 , No condensation	
Operating Altitude [m]	≤2000	
<b>GENERAL DATA</b>		
Product Dimension (W*H*D) [mm]	196*197*105	
Product Weight [kg]	3.7	4.0
Charging Cable Length [m]	5 (Standard), 6 (Optional)	
<b>SAFETY</b>		
IP protection rating	IP55	
IK protection rating	IK08	
Residual Current Detection*[mA]	DC 6	
Electrical Protection	Over/Under Voltage Protection, Overcurrent Protection, Leakage Current, Ground Protection, Surge Protection, Overtemperature Protection, Tamper Protection, PEN	
EMC	Class B	
Certification	CE/CB/RCM/UKCA	
Certification Standard	EN/IEC 61851-1: 2019, EN/IEC 61851-21-2: 2021	

\*Internal RCD-DD meets the trip time characteristics specified in IEC 62955.

\*External RCCB is required.

\*Select Type A or Type B according to local regulations.