



EP12 Plus (w)

HIGH VOLTAGE STORAGE BATTERY



- Scalable to 46.08kWh
- 100% Depth of Discharge
- Floor or Wall Mounting
- Compact & Easy Installation
- IP65 Protection Level
- High Voltage and High Efficiency



SAFETY
RELIABLE



EASY
INSTALLATION



HIGH
EFFICIENCY



EXPANDABLE
SYSTEM



100%
DOD

The EP12 Plus (w) is a high-performance, scalable battery storage system, allows for maximum flexibility, making it suitable for a broad range of storage applications.

Additional batteries can be installed in parallel allowing for a maximum storage capacity of 46.08kWh.



For more information about the Fox ESS range, visit:
au.fox-ess.com



TECHNICAL SPECIFICATIONS

MODEL	EP12 Plus (w)
ELECTRICAL CHARACTERISTICS	
Battery Type	LFP (LiFePO ₄)
Nominal Energy [kWh]	11.52
Nominal Voltage [V]	384
Usable Capacity [kWh]	11.52
Nominal Power [kW]	11.52
Operating Voltage [V]	348 ~ 438
Max.Charge/Discharge Current [A]*1	30
Recommend Charge Current [A]	15
Peak Discharge Current [A]	65 @60s
Peak Charge Current [A]	36 @5s
Battery Pack Round-Trip Efficiency [%]	≥95
Depth of Discharge [%]	100
Communication	CAN
Display	LED*5
Scalability	Max. 4 Units in Parallel
OPERATING CONDITIONS	
Installation Location	Outdoor/ Indoor
Operating Temperature [°C]	Charge: 0 ~ 55, Discharge: -10 ~ 55
Operating Temperature [°C] (warm up function on, optional)	Charge: -25 ~ 55, Discharge: -25 ~ 55
Storage Temperature [°C]	-10 ~ 40
Cooling Method	Natural Convection
Humidity [%]	5 ~ 95 (No Condensation)
Altitude [m]	Max. 3,000
PROTECTION	
Fire Protection Function	YES
MECHANICAL CHARACTERISTICS	
Dimensions (W*H*D) [mm]	710*640*185
Weight [kg]	98
CERTIFICATES	
Safety	IEC62619
EMC	EN IEC 61000-6-1/2/3/4
Transportation	UN38.3
Ingress Protection	IP65
MANUFACTURE	
Country of Manufacture	China

*1, The current is affected by temperature, cell voltage and SOC.