



# EP11

HIGH VOLTAGE STORAGE BATTERY



- Scalable to 41.6kWh
- 90% Depth of Discharge
- Floor or Wall Mounting
- Compact & Easy Installation
- IP65 Protection Level
- High Voltage and High Efficiency



SAFETY  
RELIABLE



EASY  
INSTALLATION



HIGH  
EFFICIENCY



EXPANDABLE  
SYSTEM



90%  
DOD

The EP11 is a high-performance, scalable battery storage system, allows for maximum flexibility, making it suitable for a broad range of storage applications.

Additional batteries can be installed in parallel allowing for a maximum storage capacity of 41.6kWh.



For more information about the Fox ESS range, visit  
[www.fox-ess.com](http://www.fox-ess.com)



## TECHNICAL SPECIFICATIONS

SYSTEM NAME	EP11
<b>ELECTRICAL CHARACTERISTICS</b>	
Compatible PCS	All Series of H1, KH, H3, H3-Pro, US
Battery Type	LifePO4 Prismatic Cell
Nominal Energy [kWh]	10.36
Usable Capacity [Wh]	9331
Nominal Voltage [V]	384
Nominal Power [W]	10368
Operating Voltage [V]	348 ~ 438
Max.Charge/Discharge Current [A]*1	27
Recommend Charge Current [A]	13.5
Peak Discharge Current [A]	65 @60s
Peak Charge Current [A]	32.4 @5s
Battery Pack Round-Trip Efficiency [%]	≥95
Depth of Discharge [%]	90
Cycle Life	≥4000
Communication	CAN
Display	LED*5
Scalability	Max. 4 Units in Parallel
<b>OPERATING CONDITIONS</b>	
Installation Location	Outdoor/ Indoor
Operating Temperature [°C]	Charge: 0 ~ 55 Discharge: -10 ~ 55
Storage Temperature [°C]	0~35
Cooling Method	Natural Convection
Humidity [%]	5 ~ 95 (No Condensing)
Altitude [m]	Max. 2,000
<b>MECHANICAL CHARACTERISTICS</b>	
Dimensions (W*H*D) [mm]	710*625*147
Weight [kg]	99±2
<b>CERTIFICATES</b>	
Safety	IEC62619
EMC	EN IEC 61000-6-1/3
Transportation	UN38.3
Ingress Protection	IP65
<b>MANUFACTURE</b>	
Country of origin	China

\*1, The current is affected by temperature, cell voltage and SOC.